



SHUTOUT® MANHOLE LUBRICANT & SEALANT TECHNICAL SPECIFICATION

DESCRIPTION

Cherne Shutout® seals and lubricates manhole covers to reduce inflow. **Shutout®** is a safe, jobsite ready solution compatible with most manhole installations. It is designed to enhance existing seals by filling voids and defects within the manhole cover and seat. **Shutout®** creates a water barrier between surfaces, reducing the likelihood of corrosion and lubricating the manhole cover to allow for easier and safer removal. It can be applied easily with minimal surface preparation. Monitor inflow to reapply as needed.

APPROVALS AND LISTINGS



Listed to NSF/ANSI 61



APPLICATION / USES

- Shutout is compatible with most manhole covers*
- Designed to enhance existing gaskets to provide a positive seal against inflow. Significantly reduces inflow at application
- Serves as a barrier between lid and surface, reducing corrosion and filling voids and defects in the manhole cover
- Applies easily on surfaces, requires no measurements or planning before application

*Not compatible with revolutionary access design and some T-gasket manhole installations

PROPERTIES

PHYSICAL PROPERTIES

Appearance/Color	Gray
Service Temperature	-18°C to 82°C
Application Temperature	-1°C to 66°C

PRODUCT SELECTOR

SHUTOUT® MANHOLE LUBRICANT & SEALANT

✓	Product Number	Size	Carton Quantity
	395509	10.1 fl. oz. (298mL)	12

Job Name _____	Item # _____
Location _____	
Engineer _____	Contractor _____
PO # _____	Tag _____
Representative _____	



MATERIAL SAFETY INFORMATION

FOR MORE INFORMATION ON THIS PRODUCT, REQUEST SAFETY DATA SHEET

For Delivery by Fax	Call 1-800-321-9535
Internet	See SDS section of www.Oatey.com
HMIS® Ratings	Health: 0 Flammability: 1 Physical Hazard: 0

PRECAUTIONS

All Ingredients are non-hazardous. NJ-T.S.R. 31348300 5005P, 5006P, 5007P, 5008P & 5009P. **Obtain a copy of Safety Data Sheet from distributor before use. Do not handle until all safety precautions have been read and understood. KEEP OUT OF REACH OF CHILDREN.**

FOR EMERGENCY FIRST AID HELP CALL 877-740-5015.

DIRECTIONS

Prepare manhole cover and seat surfaces by removing loose material with stiff wire brush. Wipe off excess debris and moisture. Apply approximately 3/8" continuous bead of **Shutout®** to the perimeter of seat surface. With light pressure, run finger across bead to ensure good contact to the cover seat. Replace cover. Surfaces may become slick with application, ensure proper handling, and always ensure proper PPE.

Access BIM/Revit content through www.oatey.com